

## Flexible LED strip

### AKTOFlexLine



- Samsung LEDs.



- Ultra slim (5 mm width).

- Minor voltage drop – 2 oz PCB.

- High color rendering index CRI>80.

- Low color temperature tolerances (MacAdam 3).

- Full range of colors (6500K, 4000K, 3000K, 2700K, 2000K).

- Easy installation (e.g. double-sided adhesive tape).

- Extensive use of options (e.g. for furniture, architectural, accent lighting).

- Long LEDs life time: >50 000 h.

- 5-year warranty.

- Made in Europe.



#### EXTENSIVE USE OF OPTIONS:

Accent lighting



Residential use



Commercial lighting projects



Outdoor lighting



Shop equipment



Furniture manufacturing



Lighting fixtures manufacturing



#### TECHNICAL DATA



Model	AFL-120U96245M-XW				
Dimensions, mm	1000x5x1.15				
Current, A	~0.4				
Voltage, V	24 DC				
Power, W/m	~9.6				
LED quantity, pcs	120				
Color	Cold white	Neutral white	Warm white	Warm white	Amber white
Color temperature (CCT)	6500K (-CW)	4000K (-NW)	3000K (-WW)	2700K (-WWW)	2000K (-20)
Luminous flux, Lm	1128	1150	1084	1040	1012
Color rendering index (CRI)	>80				
Light angle	120°				
Working temperature (Tc point)	-25° - +65°				
Cutting step, mm	50				
Ingress protection	IP20				
Package	5 meters				

#### TECHNICAL DRAWING (mm)

